



ROLLANT 520 RC

*South African standard specification 2024

- Fixed-chamber baler with 1.25 - 1.35 m bale chamber diameter
- 1.20 m bale width

Pick-up:

- Pick-up width 2.10 m
- 4 rows of tines, cam track controlled
- Pick-up guide wheels with 16x6.5-8 tyres
- Cross augers on both sides

ROTO CUT cutting rotor:

- Cutting rotor with four helically arranged rows of tines
- 14 knives, individually protected against foreign objects

Bale chamber:

- 16 profiled steel rollers
- Tailgate with hydraulic locking device
- Constantly lubricated baling roller bearings
- Constant chain lubrication
- Hydraulic requirements: 1 x sa and 1 x da

***South African standard specification 2024**

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.



Details of the selected product

Option		Description	Price
Crop Flow			
PR_B02/0040		Pick-up with baffle plate, pick-up width 2.10 m	Standard
PR_B06/0010	+	Castor guide wheels for pick-up, oscill. (pivot point Ø 30 mm)	Standard
PR_C06/0020		ROTO CUT cutting rotor	Standard
PR_C14/0120		Knife set	Standard
PR_C20/0010		Without MAXIMUM PRESSURE SYSTEM (MPS)	Standard
PR_H02/0020	+	ROLLATEX net wrapping	Standard
PR_G04/0310		Bale ejector, straight	Standard
Hitching			
PR_M16/0120		D40 hitch eye, MR	Standard
PR_M14/0010		Universal drawbar for bottom hitching	Standard
PR_M04/0380		Single wide-angle PTO drive shaft w/ cam clutch, 6-spline	Standard
PR_P08/0010		Input gearbox 540 rpm	Standard
PR_M12/0020		ROTO CUT hydraulic/electronic configuration	Standard
PR_M06/0010		Tractor hydraulics connection, metric	Standard
Chassis & Tyres			
PR_N10/0030	+	19.0/45-17 tyres	Standard
Machine Operation			
PR_Q06/0500		CEMIS 700	Standard
Additional Equipment			
PR_S04/0040		Tool kit	Standard
PR_S09/0010		Battery cable	Standard
PR_C05/0010		Reverse lever	Standard
PR_S02/0010		Statutory equipment	Standard
PR_S06/0030		Technical documentation, English	Standard
PR_S10/0060		Without speed sticker	Standard
PR_S12/0010		Lighting	Standard
PR_T02/0110		Mode of shipment: SKD 40'	Standard

*South African standard specification 2024

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.

PR_T03/0110

Shipment SKD, 40'

Standard

***South African standard specification 2024**

- 1) The above configuration is intended as general information.
- 2) The right to make modifications is reserved. Please always consult your CLAAS authorised importer as the sole source of current information on our vehicle's technical features.
- 3) All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.